

The performance information listed is intended to be used for reference only and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

Product	AAMA/WDMA				
	101 / I.S. 2 / A440-05				
	Config.	Max Size Tested	Hallmark Certified Performance Rating (DP)	Water Performance (psf)	Air Performance (cfm/ft2)
Clad Casement	Single Unit	30x78	LC35 standard all sizes	5.25	< 0.1
	Single Unit	36x72, 24x84, 30x77	LC50 optional some sizes	7.52	< 0.1
	Single Unit	24x84, 36x72	LC60 optional some sizes	9.00	< 0.1
Clad Casement Picture	Single Unit	84x84	LC35 standard all sizes	5.25	< 0.1
	Single Unit	72x72	LC50 optional some sizes	7.52	< 0.1
	Single Unit	48x84	LC60 optional some sizes	9.00	< 0.1
Clad Awning	Single Unit	48x48 (also tested - 60x36)	LC35 standard all sizes	5.25	< 0.1
	Single Unit	48x48	LC50 optional some sizes	7.52	< 0.1
Clad Horizontal Sliding	XX	71x60	LC30	4.50	< 0.2
Clad Double-Hung	Single Unit	45x92	LC35 standard all sizes	5.25	< 0.1
	Single Unit	45x80	LC50 optional some sizes	7.52	< 0.1
	Single Unit	41x64	LC60 optional some sizes	9.00	< 0.1
Clad Double-Hung Picture	Single Unit		LC35 standard	5.25	< 0.1
	Single Unit	77x88 (also tested - 49x92)	LC50 optional	7.52	< 0.1
Clad Direct-Set Radius	Single Unit	84x84	LC35	5.25	< 0.1
	Single Unit	68x68	LC50 option - sizes ≤ 32 sq. ft.	7.52	< 0.1
Clad 400 series Sliding Patio Door	XO	96x95.5	C35 standard	5.25	< 0.1
	XO	72x95.5	C50 optional	7.52	< 0.1
Clad 400 series Sliding Patio Door Sidelight	O	52x95.5	C35 standard	5.25	< 0.1
	O	39.5x95.5	C50 optional	7.52	< 0.1
Clad 300 series Sliding Patio Door	XO	96x95.5	LC25 standard	3.75	< 0.1
	XO	72x95.5	LC50 optional	7.52	< 0.1
Clad 300 series Sliding Patio Door Sidelight	O	38.6x95.5	LC50	7.52	< 0.1
Clad Inswing Patio Door *	X	38.6x95.5	R40	6.00	< 0.1
Clad Inswing Patio Door *	XO	77.125x95.5	R40	6.00	< 0.1
Clad Inswing Patio Door *	XOX	116x95.5	R40	6.00	< 0.1
Clad French Inswing Patio Door *	XX	77.125x95.5	R40	6.00	< 0.1
Clad Inswing Stationary Patio Door *	O	38.6x95.5	R40	6.00	< 0.1
Clad Outswing Patio Door *	X	38.6x95.5	LC50	7.52	< 0.1
Clad Outswing Patio Door *	XO	77.125x95.5	LC50	7.52	< 0.1
Clad French Outswing Patio Door *	XX	77.125x95.5	LC50	7.52	< 0.1
Clad Outswing Stationary Patio Door *	O	38.6x95.5	R50	7.52	< 0.1

* **Note:** Doors must have multi-point hardware and standard sill.

Siteline EX Primed Wood

Product	AAMA/WDMA				
	101 / I.S. 2 / A440-05				
	Config.	Max Size Tested	Hallmark Certified Performance Rating (DP)	Water Performance (psf)	Air Performance (cfm/ft2)
Primed Casement	Single Unit	24x84	LC35 standard	5.25	< 0.1
	Single Unit	36x72, 30x78, 24x84	LC50 optional some sizes	7.52	< 0.1
Primed Casement Picture	Single Unit	84x84	LC35 standard all sizes	5.25	< 0.1
	Single Unit	72x72	LC50 optional some sizes	7.52	< 0.1
Primed Awning	Single Unit	48x48 (also tested - 60x36)	LC35 standard all sizes	5.25	< 0.1
	Single Unit	48x48	LC50 optional	7.50	< 0.1
Primed Horizontal Sliding	XX	71x60	LC30	4.50	< 0.2
Primed Double-Hung	Single Unit	45x92	LC35 standard all sizes	5.25	< 0.1
	Single Unit	45x60, 33x80	LC50 optional some sizes	7.52	< 0.1
Primed Double-Hung Fixed	Single Unit	77x88	LC35 standard all sizes	5.25	< 0.1
	Single Unit	50x92	LC50 optional some sizes	7.52	< 0.1
Primed Direct-Sets	Single Unit	84x84	LC35	5.25	< 0.1
	Single Unit	68x68	LC50 option	7.52	< 0.1

Rev. 4/20/11

RELIABILITY *for real life*®

