



The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

 Highlighted options are ENERGY STAR certified in all zones.  
 Highlighted options are ENERGY STAR certified in Northern, North-Central

All door configurations achieve an air leakage rate of ≤0.3 cfm/ft <sup>2</sup> in accordance with NFRC400.								
TYPE	GLASS UNIT THICKNESS/ DESCRIPTION	GLAZING	Door illustrations are examples of glass area and are not representative of the full selection of door designs available.					
			1/4 Lite		3/4 Lite		Full Lite	
			U-Factor	SHGC	U-Factor	SHGC	U-Factor	SHGC
Inswing and Outswing	1" Glass Unit	Clear IG	0.25	0.10	0.34	0.27	0.38	0.35
		Low-E IG	0.23	0.09	0.29	0.21	0.32	0.29
		Clear IG w/ Grids	0.25	0.09	0.34	0.24	0.38	0.31
		Low-E IG w/ Grids	0.23	0.08	0.29	0.21	0.32	0.28
	Decorative Glass	Decorative Glass	0.23	0.10	0.29	0.23	-	-
	Flush / Embossed - 1-3/4" Thickness	Flush / Embossed - 1-3/4"	U-Factor = 0.19 SHGC = 0.01					
Sidelite	1" Glass Unit	Clear IG	0.18	0.03	0.26	0.15	0.29	0.19
		Low-E IG	0.17	0.02	0.23	0.13	0.26	0.16
		Clear IG w/ Grids	0.18	0.03	0.26	0.14	0.29	0.18
		Low-E IG w/ Grids	0.17	0.03	0.23	0.12	0.26	0.15
	Decorative Glass	Decorative Glass	0.17	0.03	0.24	0.14	0.27	0.18
	Flush / Embossed - 1-3/4" Thickness	Flush / Embossed - 1-3/4"	U-Factor = 0.15 SHGC = 0.01					

Performance values calculated in accordance with NFRC 100 & 200. This data is certified by NFRC and can be licensed to participating dealers. Certified product must carry a label with valid NFRC logo.