


The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

 Highlighted options meet Energy Star performance criteria.

Design Pro and Smooth Pro Fiberglass Doors												
TYPE			GLASS UNIT THICKNESS			GLAZING			Door illustrations are examples of glass area and are not representative of the full selection of door designs available.			
									1/4 Lite	1/2 Lite	3/4 Lite	Full Lite
			u-factor		SHGC		u-factor		SHGC		u-factor	
Inswing and Outswing	1/2" Glass Unit	Clear IG	0.24	0.05	0.32	0.20	0.36	0.27	0.39	0.34		
		Low-E IG	0.24	0.04	0.29	0.16	0.32	0.23	0.34	0.29		
		Clear IG w/ Grids	0.24	0.04	0.32	0.17	0.36	0.24	0.39	0.30		
		Low-E IG w/ Grids	0.24	0.04	0.29	0.15	0.32	0.20	0.34	0.25		
Inswing and Outswing	3/4" Glass Unit	Clear IG with SDL	n/a	n/a	n/a	n/a	0.34	0.22	0.37	0.26		
		Low-E IG with SDL	n/a	n/a	n/a	n/a	0.28	0.18	0.30	0.22		
Inswing and Outswing	1" Glass Unit	Clear IG	0.24	0.05	0.31	0.20	0.34	0.27	0.37	0.35		
		Low-E IG	0.19	0.03	0.25	0.16	0.28	0.23	0.30	0.28		
		Clear IG w/ Grids	0.24	0.04	0.31	0.17	0.34	0.24	0.37	0.30		
		Low-E IG w/ Grids	0.19	0.02	0.25	0.14	0.28	0.21	0.30	0.25		
		Clear IG w/ Blinds	n/a	n/a	0.29	0.19	0.34	0.28	0.37	0.34		
		Low-E IG w/ Blinds	n/a	n/a	0.26	0.16	0.30	0.23	0.32	0.28		
Inswing and Outswing	Decorative Glass	Decorative / Clear IG	0.19	0.03	0.25	0.15	0.28	0.23	0.31	0.27		
		Decorative / Low-E IG	n/a	n/a	n/a	n/a	n/a	n/a	0.29	0.23		
Inswing and Outswing	Triple Pane	Clear w/ Blinds and Grids	n/a	n/a	0.24	0.15	n/a	n/a	0.28	0.27		
		Low-E w/ Blinds and Grids	n/a	n/a	0.22	0.13	n/a	n/a	0.25	0.23		
		Clear w/ Blinds and Decorative Glass	n/a	n/a	0.23	0.14	n/a	n/a	0.26	0.25		
Inswing and Outswing	Flush / Embossed	Flush / Embossed	U-factor = 0.17 SHGC = 0.00									

Sidelite	1/2" Glass Unit	Clear IG	n/a	n/a	0.31	0.12	0.33	0.16	0.36	0.20		
		Low-E IG	n/a	n/a	0.29	0.10	0.31	0.13	0.33	0.17		
		Clear IG w/ Grids	n/a	n/a	0.31	0.11	0.33	0.15	0.36	0.19		
		Low-E IG w/ Grids	n/a	n/a	0.29	0.09	0.31	0.13	0.33	0.16		
Sidelite	3/4" Glass Unit	Clear IG with SDL	n/a	n/a	n/a	n/a	0.30	0.13	0.32	0.15		
		Low-E IG with SDL	n/a	n/a	n/a	n/a	0.28	0.10	0.30	0.13		
Sidelite	1" Glass Unit	Clear IG	n/a	n/a	0.30	0.12	0.32	0.16	0.35	0.20		
		Low-E IG	n/a	n/a	0.24	0.08	0.27	0.11	0.28	0.14		
		Clear IG w/ Grids	n/a	n/a	0.30	0.11	0.32	0.15	0.35	0.19		
		Low-E IG w/ Grids	n/a	n/a	0.24	0.07	0.27	0.11	0.28	0.13		
		Clear IG w/ Blinds	n/a	n/a	0.27	0.09	0.30	0.14	0.33	0.16		
		Low-E IG w/ Blinds	n/a	n/a	0.26	0.08	0.29	0.11	0.30	0.14		
Sidelite	Decorative Glass	Decorative / Clear IG	n/a	n/a	0.24	0.08	0.27	0.12	0.30	0.14		
		Decorative / Low-E IG	n/a	n/a	n/a	n/a	n/a	n/a	0.29	0.12		
Sidelite	Flush / Embossed	Flush / Embossed	U-factor = 0.19 SHGC = 0.00									