

# MOLDED DOOR SIZE AND PROFILE OPTIONS

6'8" and 7'0" Doors	1'0"	1'2"	1'3"	1'4"	1'6"	1'8"	1'10"	2'0"	2'2"	2'4"	2'6"	2'8"	2'10"	3'0"	Sticking Profile	ProCore®	Bifolds
AVALON® 6'8" Oak Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
AVALON® 7'0" Oak Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CAIMAN® 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CAIMAN® 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CAMBRIDGE™ 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CAMBRIDGE™ 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CAMDEN® 6'8" Oak Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CAMDEN® 7'0" Oak Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CARRARA® 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CARRARA® 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CASHAL® 6'8" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	X
CASHAL® 7'0" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	X
COLONIAL™ 6'8" Pine Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
COLONIAL™ 7'0" Pine Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
COLONIST® 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
COLONIST® 7'0" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	X
COLONIST® 6'8" Pine Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
COLONIST® 7'0" Pine Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CONMORE® 6'8" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	S	X	X
CONMORE® 7'0" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	S	X	X
CONTINENTAL™ 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CONTINENTAL™ 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CORVADO® 6'8" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	X
CORVADO® 7'0" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	X
COVENTRY® 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
COVENTRY® 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CRAFTSMAN III™ 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	C	X	X
CRAFTSMAN III™ 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	C	X	X
IMPRESSION™ Colonist® 6'8" Pine Grain or Smooth	-	-	-	-	-	-	-	X	-	X	X	X	-	X	CB	-	-
IMPRESSION™ Colonist® 7'0" Pine Grain or Smooth	-	-	-	-	-	-	-	X	-	X	X	X	-	X	CB	-	-
MADISON® 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	C	X	X
MADISON® 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	C	X	X
MONROE 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	C	X	X
MONROE 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	C	X	X
PRINCETON™ 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
PRINCETON™ 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
PROVINCIAL® 6'8" Pine Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
PROVINCIAL® 7'0" Pine Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
ROCKPORT™ 6'8" Smooth	-	-	-	-	X	X	-	X	X	X	X	X	X	X	CB	X	X
ROCKPORT™ 7'0" Smooth	-	-	-	-	X	X	-	X	X	X	X	X	X	X	CB	X	X
SANTA FE™ 6'8" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
SANTA FE™ 7'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

Please check your local distributor for availability of 7'0" and 8'0" doors in your area.

For more detailed product specifications, please check out our JELD-WEN product line at [www.jeld-wen.com](http://www.jeld-wen.com).

# MOLDED DOOR SIZE AND PROFILE OPTIONS

8'0" Doors	1'0"	1'2"	1'3"	1'4"	1'6"	1'8"	1'10"	2'0"	2'2"	2'4"	2'6"	2'8"	2'10"	3'0"	Sticking Profile	ProCore®	Bifolds
CAIMAN® 8'0" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	-
CAMBRIDGE™ 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X
CARRARA® 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CASHAL® 8'0" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	X
COLONIAL™ 8'0" Pine Grain	-	-	-	-	X	X	X	X	X	X	X	X	-	X	O	X	X
COLONIST® 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
COLONIST® 8'0" Pine Grain	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
CONTINENTAL™ 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	-
CORVADO® 8'0" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	X
COVENTRY™ 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
MADISON® 8'0" Smooth	-	-	-	X	X	X	X	X	X	X	X	X	X	X	C	X	X
MONROE 8'0" Smooth	-	-	-	X	X	X	X	X	X	X	X	X	X	X	C	X	X
PRINCETON™ 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	CB	X	X
ROCKPORT™ 8'0" Smooth	-	-	-	-	X	X	X	X	X	X	X	X	X	X	CB	X	-
SANTA FE™ 8'0" Smooth	X	X	X	X	X	X	X	X	X	X	X	X	X	X	O	X	X


Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

Please check your local distributor for availability of 7'0" and 8'0" doors in your area.

For more detailed product specifications, please check out our JELD-WEN product line at [www.jeld-wen.com](http://www.jeld-wen.com).


# 6'8" AND 7'0" DOORS

## AVALON®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	6-3/16"	2-29/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-7/8" (6'8") 9-7/8" (7'0")	CB	Oak Grain
1'2" 1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7-11/16"	3-5/32" (1'2") 3-21/32" (1'3") 4-5/32" (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-7/8" (6'8") 9-7/8" (7'0")	CB	Oak Grain
1'6" 1'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	8-3/4"	4-5/8" (1'6") 5-5/8" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-7/8" (6'8") 9-7/8" (7'0")	CB	Oak Grain
1'10" 2'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-7/8" (6'8") 9-7/8" (7'0")	CB	Oak Grain
2'2" 2'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	19-5/8"	3-3/16" (2'2") 4-3/16" (2'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-7/8" (6'8") 9-7/8" (7'0")	CB	Oak Grain
2'6"	6'8" 7'0"	Three	1-3/8" 1-3/4"	21-5/8"	4-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-7/8" (6'8") 9-7/8" (7'0")	CB	Oak Grain
2'8" 2'10"	6'8" 7'0"	Three	1-3/8" 1-3/4"	23-5/8"	4-3/16" (2'8") 5-3/16" (2'10")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-7/8" (6'8") 9-7/8" (7'0")	CB	Oak Grain
3'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	27-5/8"	4-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	7-7/8" (6'8") 9-7/8" (7'0")	CB	Oak Grain

## CAIMAN®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
1'10" 2'0" 2'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	15-3/4"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	17-3/4"	5-1/8"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-3/4"	5-1/8"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'8" 2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21-3/4"	5-1/8" (2'8") 6-1/8" (2'10")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	23-3/4"	6-1/8"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo


\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

## CAMBRIDGE™



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	5-9/16"	3-7/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7-9/16"	3-7/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'3"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-9/16"	3-7/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-9/16"	3-7/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	11-9/16"	3-7/32" (1'6") 4-7/32" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
1'10" 2'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	13-11/16"	4-5/32" (1'10") 5-5/32" (2'0")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
2'2" 2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	17-11/16"	4-5/32" (2'2") 5-5/32" (2'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-11/16"	5-5/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
2'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21-11/16"	5-5/32"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth
2'10" 3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	23-3/4"	5-1/8" (2'10") 6-1/8" (3'0")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Smooth

## CAMDEN®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	6-11/16"	2-21/32"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/8" (6'8") 10-1/8" (7'0")	CB	Oak Grain
1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7-1/2"	3-1/4" (1'2") 3-3/4" (1'3") 4-1/4" (1'4")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/8" (6'8") 10-1/8" (7'0")	CB	Oak Grain
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-1/2"	4-1/4" (1'6") 5-1/4" (1'8")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/8" (6'8") 10-1/8" (7'0")	CB	Oak Grain
1'10" 2'0" 2'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	14-15/16"	3-17/32" (1'0") 4-17/32" (2'0") 5-17/32" (2'2")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/8" (6'8") 10-1/8" (7'0")	CB	Oak Grain
2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	18-1/8"	4-15/16"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/8" (6'8") 10-1/8" (7'0")	CB	Oak Grain
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-11/16"	5-5/32"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/8" (6'8") 10-1/8" (7'0")	CB	Oak Grain
2'8" 2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	22-13/16"	4-19/32" (2'8") 5-19/32" (2'10")	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/8" (6'8") 10-1/8" (7'0")	CB	Oak Grain
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	25"	5-1/2"	N/A	5-3/8" (6'8") 7-3/8" (7'0")	3-3/4"	8-1/8" (6'8") 10-1/8" (7'0")	CB	Oak Grain

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


# 6'8" AND 7'0" DOORS

## CARRARA®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
1'10" 2'0" 2'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0") 5-3/16" (2'2")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	17-5/8"	5-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-5/8"	5-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'8" 2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21-5/8"	5-3/16" (2'8") 6-3/16" (2'10")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	23-5/8"	6-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth

## CASHAL®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
1'10" 2'0" 2'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0") 5-3/16" (2'2")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-5/8"	4-3/16"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21-5/8"	4-3/16"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'8" 2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	23-5/8"	4-3/16" (2'8") 5-3/16" (2'10")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	25-5/8"	5-3/16"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo


\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

## COLONIAL™



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Pine Grain
1'6" 1'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	11-9/16"	3-7/32" (1'6") 4-7/32" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Pine Grain
1'10" 2'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	5-9/16"	3-1/4" (1'10") 4-1/4" (2'0")	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Pine Grain
2'2" 2'4"	6'8" 7'0"	Six	1-3/8" 1-3/4"	7-9/16"	3-1/4" (2'2") 4-1/4" (2'4")	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Pine Grain
2'6"	6'8" 7'0"	Six	1-3/8" 1-3/4"	8-9/16"	4-1/4"	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Pine Grain
2'8"	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-9/16"	4-1/4"	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Pine Grain
2'10"	6'8" 7'0"	Six	1-3/8" 1-3/4"	10-9/16"	4-1/4"	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Pine Grain
3'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	11-9/16"	4-1/4"	4-3/8"	4-1/4" (6'8") 6-1/4" (7'0")	7"	9-1/8" (6'8") 11-1/8" (7'0")	O	Pine Grain

## COLONIST®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/4"	6-3/4"	8-1/4"	CB	Smooth
1'6" 1'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
1'10" 2'0" 2'2"	6'8" 7'0"	Six	1-3/8" 1-3/4"	6"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'4"	6'8" 7'0"	Six	1-3/8" 1-3/4"	8"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'6"	6'8" 7'0"	Six	1-3/8" 1-3/4"	9"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'8" 2'10"	6'8" 7'0"	Six	1-3/8" 1-3/4"	10"	4-1/8" (2'8") 5-1/8" (2'10")	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
3'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	12"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


# 6'8" AND 7'0" DOORS

## COLONIST®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Pine Grain
1'6" 1'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	11-7/8"	3-1/16" (1'6") 4-1/16" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Pine Grain
1'10" 2'0" 2'2"	6'8" 7'0"	Six	1-3/8" 1-3/4"	6"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Pine Grain
2'4"	6'8" 7'0"	Six	1-3/8" 1-3/4"	8"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Pine Grain
2'6"	6'8" 7'0"	Six	1-3/8" 1-3/4"	9"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Pine Grain
2'8" 2'10"	6'8" 7'0"	Six	1-3/8" 1-3/4"	10"	4-1/8" (2'8") 5-1/8" (2'10")	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Pine Grain
3'0"	6'8" 7'0"	Six	1-3/8" 1-3/4"	12"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-3/4"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Pine Grain

## CONMORE®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Panel Type	Sticking Profile	Surface
1'6" 1'8"	6'8" 7'0"	Five	1-3/8" 1-3/4"	9-5/8"	4-3/16" (1'6") 5-3/16" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	S	Smooth
1'10" 2'0" 2'2"	6'8" 7'0"	Five	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0") 5-3/16" (2'2")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	S	Smooth
2'4"	6'8" 7'0"	Five	1-3/8" 1-3/4"	19-5/8"	4-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	S	Smooth
2'6"	6'8" 7'0"	Five	1-3/8" 1-3/4"	21-5/8"	4-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	S	Smooth
2'8" 2'10"	6'8" 7'0"	Five	1-3/8" 1-3/4"	23-5/8"	4-3/16" (2'8") 5-3/16" (2'10")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	S	Smooth
3'0"	6'8" 7'0"	Five	1-3/8" 1-3/4"	25-5/8"	5-3/16"	N/A	4-1/4" (6'8") 6-1/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	S	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo


\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

## CONTINENTAL™



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	5-9/16"	3-7/32" (1'0")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-9/16"	2-23/32" (1'2") 3-7/32" (1'3") 3-23/32" (1'4")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	10-9/16"	3-23/32" (1'6") 4-23/32" (1'8")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
1'10" 2'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	14"	4" (1'10") 5" (2'0")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
2'2" 2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	18"	4" (2'2") 5" (2'4")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	20"	5"	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
2'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21"	5-1/2"	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth
2'10" 3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	24"	5" (2'10") 6" (3'0")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth

## CORVADO®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	4-3/16" (6'8") 6-3/16" (7'0")	6-5/8"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
1'10" 2'0" 2'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0") 5-3/16" (2'2")	N/A	4-3/16" (6'8") 6-3/16" (7'0")	6-5/8"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-5/8"	4-3/16"	N/A	4-3/16" (6'8") 6-3/16" (7'0")	6-5/8"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21-5/8"	4-3/16"	N/A	4-3/16" (6'8") 6-3/16" (7'0")	6-5/8"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
2'8" 2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	23-5/8"	4-3/16" (2'8") 5-3/16" (2'10")	N/A	4-3/16" (6'8") 6-3/16" (7'0")	6-5/8"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	25-5/8"	5-3/16"	N/A	4-3/16" (6'8") 6-3/16" (7'0")	6-5/8"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth


Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.




# 6'8" AND 7'0" DOORS

## COVENTRY®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-13/16"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	4-1/4" (6'8") 6-1/4" (7'0")	6-13/16"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
1'10" 2'0" 2'2"	6'8" 7'0"	Four	1-3/8" 1-3/4"	6"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-13/16"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'4"	6'8" 7'0"	Four	1-3/8" 1-3/4"	8"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-13/16"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'6"	6'8" 7'0"	Four	1-3/8" 1-3/4"	9"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-13/16"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
2'8" 2'10"	6'8" 7'0"	Four	1-3/8" 1-3/4"	10"	4-1/8" (2'8") 5-1/8" (2'10")	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-13/16"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth
3'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	12"	4-1/8"	3-3/4"	4-1/4" (6'8") 6-1/4" (7'0")	6-13/16"	8-1/4" (6'8") 10-1/4" (7'0")	CB	Smooth

## CRAFTSMAN III™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Panel Type	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	4"	4"	N/A	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
1'2" 1'3"	6'8" 7'0"	Two	1-3/8" 1-3/4"	6"	4" (1'2") 4-1/2" (1'3")	N/A	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-1/4"	3-7/8"	N/A	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
1'6" 1'8" 1'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	10"	4" (1'6") 5" (1'8") 6" (1'10")	N/A	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
2'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	15"	4-1/2"	4-1/2"	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
2'2" 2'4"	6'8" 7'0"	Three	1-3/8" 1-3/4"	17"	4-1/2" (2'2") 5-1/2" (2'4")	4-1/2"	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
2'6" 2'8"	6'8" 7'0"	Three	1-3/8" 1-3/4"	21"	4-1/2" (2'6") 5-1/2" (2'8")	4-1/2"	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth
2'10" 3'0"	6'8" 7'0"	Three	1-3/8" 1-3/4"	25"	4-1/2" (2'10") 5-1/2" (3'0")	4-1/2"	4-5/8" (6'8") 6-5/8" (7'0")	N/A	8-15/16" (6'8") 10-15/16" (7'0")	Flat	C	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo


\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

## IMPRESSION™ MIRROR DOOR



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Panel Type	Sticking Profile	Surface
2'0"	6'8"	One	1-3/8"	15-3/8"	4-1/4"	N/A	4-1/4"	N/A	9-3/8"	Flat	CB	Pine Grain or Smooth
2'4"	6'8"	One	1-3/8"	19-3/8"	4-5/16"	N/A	4-1/4"	N/A	9-3/8"	Flat	CB	Pine Grain or Smooth
2'6"	6'8"	One	1-3/8"	21-3/8"	4-5/16"	N/A	4-1/4"	N/A	9-3/8"	Flat	CB	Pine Grain or Smooth
2'8"	6'8"	One	1-3/8"	23-3/8"	4-5/16"	N/A	4-1/4"	N/A	9-3/8"	Flat	CB	Pine Grain or Smooth
3'0"	6'8"	One	1-3/8"	27-3/8"	4-5/16"	N/A	4-1/4"	N/A	9-3/8"	Flat	CB	Pine Grain or Smooth

## MADISON®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Panel Type	Sticking Profile	Surface
1'0" 1'2" 1'3"	6'8" 7'0"	One	1-3/8" 1-3/4"	5-3/8"	3-5/16" (1'0") 4-5/16" (1'2") 4-13/16" (1'3")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	C	Smooth
1'4" 1'6"	6'8" 7'0"	One	1-3/8" 1-3/4"	7-13/16"	4-3/32" (1'4") 5-3/32" (1'6")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	C	Smooth
1'8" 1'10"	6'8" 7'0"	One	1-3/8" 1-3/4"	11-1/2"	4-1/4" (1'8") 5-1/4" (1'10")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	C	Smooth
2'0" 2'2"	6'8" 7'0"	One	1-3/8" 1-3/4"	15-1/2"	4-1/4" (2'0") 5-1/4" (2'2")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	C	Smooth
2'4"	6'8" 7'0"	One	1-3/8" 1-3/4"	18-1/2"	4-3/4"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	C	Smooth
2'6"	6'8" 7'0"	One	1-3/8" 1-3/4"	20-1/2"	4-3/4"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	C	Smooth
2'8" 2'10"	6'8" 7'0"	One	1-3/8" 1-3/4"	22-1/2"	4-3/4" (2'8") 5-3/4" (2'10")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	C	Smooth
3'0"	6'8" 7'0"	One	1-3/8" 1-3/4"	26-1/2"	4-3/4"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	N/A	8-1/4" (6'8") 10-1/4" (7'0")	Flat	C	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


# 6'8" AND 7'0" DOORS

## MONROE



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	6"	3"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth
1'2" 1'3"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7-1/2"	3-1/2" (1'2") 3-3/4" (1'3")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth
1'4" 1'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-1/4"	3-3/8" (1'4") 4-3/8" (1'6")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth
1'8" 1'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	11-1/2"	4-1/4" (1'8") 5-1/4" (1'10")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth
2'0" 2'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	15-1/2"	4-1/4" (2'0") 5-1/4" (2'2")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth
2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	18-1/2"	4-3/4"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	20-1/2"	4-3/4"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth
2'8" 2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	22-1/2"	4-3/4" (2'8") 5-3/4" (2'10")	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	26-1/2"	4-3/4"	N/A	4-3/4" (6'8") 6-3/4" (7'0")	7"	11-1/8" (6'8") 13-1/8" (7'0")	C	Smooth

## PRINCETON™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	6-11/16"	2-21/32" (1'0") 3-21/32" (1'2")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	3-11/16"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-9/16"	3-7/32" (1'3") 3-23/32" (1'4")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	3-11/16"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-1/2"	4-1/4" (1'6") 5-1/4" (1'8")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	3-11/16"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
1'10" 2'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	15"	3-1/2" (1'10") 4-1/2" (2'0")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	3-11/16"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
2'2" 2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	18-3/16"	3-29/32" (2'2") 4-29/32" (2'4")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	3-11/16"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	19-3/4"	5-1/8"	N/A	5-1/4" (6'8") 7-1/4" (7'0")	3-11/16"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
2'8" 2'10"	6'8" 7'0"	Two	1-3/8" 1-3/4"	22-7/8"	4-9/16" (2'8") 5-9/16" (2'10")	N/A	5-1/4" (6'8") 7-1/4" (7'0")	3-11/16"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth
3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	25-1/16"	5-15/32"	N/A	5-1/4" (6'8") 7-1/4" (7'0")	3-11/16"	8-3/16" (6'8") 10-3/16" (7'0")	CB	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo


\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

## PROVINCIAL®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	5-9/16"	3-7/32"	N/A	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
1'2"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7-9/16"	3-7/32"	N/A	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
1'3"	6'8" 7'0"	Two	1-3/8" 1-3/4"	8-9/16"	3-7/32"	N/A	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	9-9/16"	3-7/32"	N/A	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	11-9/16"	3-7/32" (1'6") 4-7/32" (1'8")	N/A	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
1'10" 2'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	5-9/16"	3-1/4" (1'10") 4-1/4" (2'0")	4-3/8"	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
2'2" 2'4"	6'8" 7'0"	Four	1-3/8" 1-3/4"	7-9/16"	3-1/4" (2'2") 4-1/4" (2'4")	4-3/8"	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
2'6"	6'8" 7'0"	Four	1-3/8" 1-3/4"	8-9/16"	4-1/4"	4-3/8"	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
2'8"	6'8" 7'0"	Four	1-3/8" 1-3/4"	9-9/16"	4-1/4"	4-3/8"	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
2'10"	6'8" 7'0"	Four	1-3/8" 1-3/4"	10-9/16"	4-1/4"	4-3/8"	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain
3'0"	6'8" 7'0"	Four	1-3/8" 1-3/4"	11-9/16"	4-1/4"	4-3/8"	5-1/8" (6'8") 7" (7'0")	7"	9" (6'8") 11-1/8" (7'0")	O	Pine Grain

## ROCKPORT™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6" 1'8"	6'8" 7'0"	Five	1-3/8" 1-3/4"	10-1/4"	3-7/8" (1'6") 4-7/8" (1'8")	N/A	4-5/8" (6'8") 6-1/2" (7'0")	N/A	8-3/8" (6'8") 10-1/2" (7'0")	CB	Smooth
2'0"	6'8" 7'0"	Five	1-3/8" 1-3/4"	15-3/4"	4-1/8"	N/A	4-5/8" (6'8") 6-1/2" (7'0")	N/A	8-3/8" (6'8") 10-1/2" (7'0")	CB	Smooth
2'2" 2'4"	6'8" 7'0"	Five	1-3/8" 1-3/4"	19-3/4"	3-1/8" (2'2") 4-1/8" (2'4")	N/A	4-5/8" (6'8") 6-1/2" (7'0")	N/A	8-3/8" (6'8") 10-1/2" (7'0")	CB	Smooth
2'6"	6'8" 7'0"	Five	1-3/8" 1-3/4"	21-3/4"	4-1/8"	N/A	4-5/8" (6'8") 6-1/2" (7'0")	N/A	8-3/8" (6'8") 10-1/2" (7'0")	CB	Smooth
2'8"	6'8" 7'0"	Five	1-3/8" 1-3/4"	23-3/4"	4-1/8"	N/A	4-5/8" (6'8") 6-1/2" (7'0")	N/A	8-3/8" (6'8") 10-1/2" (7'0")	CB	Smooth
2'10" 3'0"	6'8" 7'0"	Five	1-3/8" 1-3/4"	25-3/4"	4-1/8" (2'10") 5-1/8" (3'0")	N/A	4-5/8" (6'8") 6-1/2" (7'0")	N/A	8-3/8" (6'8") 10-1/2" (7'0")	CB	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

# 6'8" AND 7'0" DOORS

## SANTA FE™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
1'6" 1'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	10"	4" (1'6") 5" (1'8")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
1'10" 2'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	14"	4" (1'10") 5" (2'0")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
2'2" 2'4"	6'8" 7'0"	Two	1-3/8" 1-3/4"	18"	4" (2'2") 5" (2'4")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
2'6"	6'8" 7'0"	Two	1-3/8" 1-3/4"	21"	4-1/2"	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
2'8"	6'8" 7'0"	Two	1-3/8" 1-3/4"	23"	4-1/2"	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth
2'10" 3'0"	6'8" 7'0"	Two	1-3/8" 1-3/4"	24"	5" (2'10") 6" (3'0")	N/A	4-3/8" (6'8") 6-3/8" (7'0")	7"	9-7/8" (6'8") 11-7/8" (7'0")	O	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


# 8'0" DOORS

## CAIMAN®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
1'10" 2'0" 2'2"	8'0"	Two	1-3/8" 1-3/4"	15-3/4"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
2'4"	8'0"	Two	1-3/8" 1-3/4"	17-3/4"	5-1/8"	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	19-3/4"	5-1/8"	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
2'8" 2'10"	8'0"	Two	1-3/8" 1-3/4"	21-3/4"	5-1/8" (2'8") 6-1/8" (2'10")	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
3'0"	8'0"	Two	1-3/8" 1-3/4"	23-3/4"	6-1/8"	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth

## CAMBRIDGE™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-7/16"	7"	8-15/16"	O	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	9-3/4"	4-1/8" (1'6") 5-1/8" (1'8")	N/A	4-7/16"	7"	8-15/16"	O	Smooth
1'10" 2'0"	8'0"	Two	1-3/8" 1-3/4"	13-11/16"	4-5/32" (1'10") 5-5/32" (2'0")	N/A	4-7/16"	7"	8-15/16"	O	Smooth
2'2" 2'4"	8'0"	Two	1-3/8" 1-3/4"	17-11/16"	4-5/32" (2'2") 5-5/32" (2'4")	N/A	4-7/16"	7"	8-15/16"	O	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	19-11/16"	5-5/32"	N/A	4-7/16"	7"	8-15/16"	O	Smooth
2'8"	8'0"	Two	1-3/8" 1-3/4"	21-11/16"	5-5/32"	N/A	4-7/16"	7"	8-15/16"	O	Smooth
2'10" 3'0"	8'0"	Two	1-3/8" 1-3/4"	23-11/16"	5-5/32" (2'10") 6-5/32" (3'0")	N/A	4-7/16"	7"	8-15/16"	O	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


# 8'0" DOORS

## CARRARA®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	5-1/4"	6-13/16"	8-1/4"	CB	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	5-1/4"	6-13/16"	8-1/4"	CB	Smooth
1'10" 2'0" 2'2"	8'0"	Two	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0") 5-3/16" (2'2")	N/A	5-1/4"	6-13/16"	8-1/4"	CB	Smooth
2'4"	8'0"	Two	1-3/8" 1-3/4"	17-5/8"	5-3/16"	N/A	5-1/4"	6-13/16"	8-1/4"	CB	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	19-5/8"	5-3/16"	N/A	5-1/4"	6-13/16"	8-1/4"	CB	Smooth
2'8" 2'10"	8'0"	Two	1-3/8" 1-3/4"	21-5/8"	5-3/16" (2'8") 6-3/16" (2'10")	N/A	5-1/4"	6-13/16"	8-1/4"	CB	Smooth
3'0"	8'0"	Two	1-3/8" 1-3/4"	23-5/8"	6-3/16"	N/A	5-1/4"	6-13/16"	8-1/4"	CB	Smooth

## CASHAL®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
1'10" 2'0" 2'2"	8'0"	Two	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0") 5-3/16" (2'2")	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
2'4"	8'0"	Two	1-3/8" 1-3/4"	19-5/8"	4-3/16"	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	21-5/8"	4-3/16"	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
2'8" 2'10"	8'0"	Two	1-3/8" 1-3/4"	23-5/8"	4-3/16" (2'8") 5-3/16" (2'10")	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth
3'0"	8'0"	Two	1-3/8" 1-3/4"	25-5/8"	5-3/16"	N/A	6-3/4"	6-3/4"	8-1/4"	CB	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo


\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

## COLONIAL™



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6"	8'0"	Three	1-3/8" 1-3/4"	9-9/16"	4-7/32"	N/A	4-1/4"	7"	9"	O	Pine Grain
1'8"	8'0"	Three	1-3/8" 1-3/4"	11-9/16"	4-7/32"	N/A	4-1/4"	7"	9"	O	Pine Grain
1'10" 2'0"	8'0"	Six	1-3/8" 1-3/4"	5-9/16"	3-1/4" (1'10") 4-1/4" (2'0")	4-3/8"	4-1/4"	7"	9"	O	Pine Grain
2'2" 2'4"	8'0"	Six	1-3/8" 1-3/4"	7-9/16"	3-1/4" (2'2") 4-1/4" (2'4")	4-3/8"	4-1/4"	7"	9"	O	Pine Grain
2'6"	8'0"	Six	1-3/8" 1-3/4"	8-9/16"	4-1/4"	4-3/8"	4-1/4"	7"	9"	O	Pine Grain
2'8"	8'0"	Six	1-3/8" 1-3/4"	9-9/16"	4-1/4"	4-3/8"	4-1/4"	7"	9"	O	Pine Grain
3'0"	8'0"	Six	1-3/8" 1-3/4"	11-9/16"	4-1/4"	4-3/8"	4-1/4"	7"	9"	O	Pine Grain

## COLONIST®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	5-1/4"	6-3/4"	8-1/4"	CB	Smooth
1'6" 1'8"	8'0"	Three	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	5-1/4"	6-3/4"	8-1/4"	CB	Smooth
1'10" 2'0" 2'2"	8'0"	Six	1-3/8" 1-3/4"	6"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Smooth
2'4"	8'0"	Six	1-3/8" 1-3/4"	8"	4-1/8"	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Smooth
2'6"	8'0"	Six	1-3/8" 1-3/4"	9"	4-1/8"	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Smooth
2'8" 2'10"	8'0"	Six	1-3/8" 1-3/4"	10"	4-1/8" (2'8") 5-1/8" (2'10")	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Smooth
3'0"	8'0"	Six	1-3/8" 1-3/4"	12"	4-1/8"	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Smooth


Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.




# 8'0" DOORS

## COLONIST®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Three	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-1/4"	7"	8-1/4"	CB	Pine Grain
1'6" 1'8"	8'0"	Three	1-3/8" 1-3/4"	9-3/4"	4-1/8" (1'6") 5-1/8" (1'8")	N/A	4-1/4"	7"	8-1/4"	CB	Pine Grain
1'10" 2'0" 2'2"	8'0"	Six	1-3/8" 1-3/4"	6"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Pine Grain
2'4"	8'0"	Six	1-3/8" 1-3/4"	8"	4-1/8"	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Pine Grain
2'6"	8'0"	Six	1-3/8" 1-3/4"	9"	4-1/8"	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Pine Grain
2'8" 2'10"	8'0"	Six	1-3/8" 1-3/4"	10"	4-1/8" (2'8") 5-1/8" (2'10")	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Pine Grain
3'0"	8'0"	Six	1-3/8" 1-3/4"	12"	4-1/8"	3-3/4"	5-1/4"	6-3/4"	8-1/4"	CB	Pine Grain

## CONTINENTAL™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	5-1/4"	4-1/4"	11"	O	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	9-3/4"	4-1/8" (1'6") 5-1/8" (1'8")	N/A	5-1/4"	4-1/4"	11"	O	Smooth
1'10" 2'0" 2'2"	8'0"	Two	1-3/8" 1-3/4"	14"	4" (1'10") 5" (2'0") 6" (2'2")	N/A	5-1/4"	4-1/4"	11"	O	Smooth
2'4"	8'0"	Two	1-3/8" 1-3/4"	18"	5"	N/A	5-1/4"	4-1/4"	11"	O	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	20"	5"	N/A	5-1/4"	4-1/4"	11"	O	Smooth
2'8" 2'10" 3'0"	8'0"	Two	1-3/8" 1-3/4"	24"	5" (2'8") 5" (2'10") 6" (3'0")	N/A	5-1/4"	4-1/4"	11"	O	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo


\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

## CORVADO®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	5-3/16"	6-5/8"	8-3/16"	CB	Smooth
1'10" 2'0" 2'2"	8'0"	Two	1-3/8" 1-3/4"	15-5/8"	3-3/16" (1'10") 4-3/16" (2'0") 5-3/16" (2'2")	N/A	5-3/16"	6-5/8"	8-3/16"	CB	Smooth
2'4"	8'0"	Two	1-3/8" 1-3/4"	19-5/8"	4-3/16"	N/A	5-3/16"	6-5/8"	8-3/16"	CB	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	21-5/8"	4-3/16"	N/A	5-3/16"	6-5/8"	8-3/16"	CB	Smooth
2'8" 2'10"	8'0"	Two	1-3/8" 1-3/4"	23-5/8"	4-3/16" (2'8") 5-3/16" (2'10")	N/A	5-3/16"	6-5/8"	8-3/16"	CB	Smooth
3'0"	8'0"	Two	1-3/8" 1-3/4"	25-5/8"	5-3/16"	N/A	5-3/16"	6-5/8"	8-3/16"	CB	Smooth

## COVENTRY®




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	5-1/4"	6-5/8"	8-1/4"	CB	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	12"	3" (1'6") 4" (1'8")	N/A	5-1/4"	6-5/8"	8-1/4"	CB	Smooth
1'10" 2'0" 2'2"	8'0"	Four	1-3/8" 1-3/4"	6"	3-1/8" (1'10") 4-1/8" (2'0") 5-1/8" (2'2")	N/A	5-1/4"	6-5/8"	8-1/4"	CB	Smooth
2'4"	8'0"	Four	1-3/8" 1-3/4"	8"	4-1/8"	N/A	5-1/4"	6-5/8"	8-1/4"	CB	Smooth
2'6"	8'0"	Four	1-3/8" 1-3/4"	9"	4-1/8"	N/A	5-1/4"	6-5/8"	8-1/4"	CB	Smooth
2'8" 2'10"	8'0"	Four	1-3/8" 1-3/4"	10"	4-1/8" (2'8") 5-1/8" (2'10")	N/A	5-1/4"	6-5/8"	8-1/4"	CB	Smooth
3'0"	8'0"	Four	1-3/8" 1-3/4"	12"	4-1/8"	N/A	5-1/4"	6-5/8"	8-1/4"	CB	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.


# 8'0" DOORS

## MADISON®



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Panel Type	Sticking Profile	Surface
1'4" 1'6"	8'0"	One	1-3/8" 1-3/4"	7-13/16"	4-3/32" (1'4") 5-3/32" (1'6")	N/A	4-3/4"	N/A	10-1/4"	Flat	C	Smooth
1'8" 1'10"	8'0"	One	1-3/8" 1-3/4"	11-1/2"	4-1/4" (1'8") 5-1/4" (1'10")	N/A	4-3/4"	N/A	10-1/4"	Flat	C	Smooth
2'0" 2'2"	8'0"	One	1-3/8" 1-3/4"	15-1/2"	4-1/4" (2'0") 5-1/4" (2'2")	N/A	4-3/4"	N/A	10-1/4"	Flat	C	Smooth
2'4"	8'0"	One	1-3/8" 1-3/4"	18-1/2"	4-3/4"	N/A	4-3/4"	N/A	10-1/4"	Flat	C	Smooth
2'6"	8'0"	One	1-3/8" 1-3/4"	20-1/2"	4-3/4"	N/A	4-3/4"	N/A	10-1/4"	Flat	C	Smooth
2'8" 2'10"	8'0"	One	1-3/8" 1-3/4"	22-1/2"	4-3/4" (2'8") 5-3/4" (2'10")	N/A	4-3/4"	N/A	10-1/4"	Flat	C	Smooth
3'0"	8'0"	One	1-3/8" 1-3/4"	26-1/2"	4-3/4"	N/A	4-3/4"	N/A	10-1/4"	Flat	C	Smooth

## MONROE




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'4" 1'6"	8'0"	Two	1-3/8" 1-3/4"	9-1/4"	3-3/8" (1'4") 4-3/8" (1'6")	N/A	4-3/4"	7"	11-1/8"	C	Smooth
1'8" 1'10"	8'0"	Two	1-3/8" 1-3/4"	11-1/2"	4-1/4" (1'8") 5-1/4" (1'10")	N/A	4-3/4"	7"	11-1/8"	C	Smooth
2'0" 2'2"	8'0"	Two	1-3/8" 1-3/4"	15-1/2"	4-1/4" (2'0") 5-1/4" (2'2")	N/A	4-3/4"	7"	11-1/8"	C	Smooth
2'4"	8'0"	Two	1-3/8" 1-3/4"	18-1/2"	4-3/4"	N/A	4-3/4"	7"	11-1/8"	C	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	20-1/2"	4-3/4"	N/A	4-3/4"	7"	11-1/8"	C	Smooth
2'8" 2'10"	8'0"	Two	1-3/8" 1-3/4"	22-1/2"	4-3/4" (2'8") 5-3/4" (2'10")	N/A	4-3/4"	7"	11-1/8"	C	Smooth
3'0"	8'0"	Two	1-3/8" 1-3/4"	26-1/2"	4-3/4"	N/A	4-3/4"	7"	11-1/8"	C	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo


\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

**PRINCETON™**



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	5-1/4"	3-3/4"	8-1/4"	CB	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	9-1/2"	4-1/4" (1'6") 5-1/4" (1'8")	N/A	5-1/4"	3-3/4"	8-1/4"	CB	Smooth
1'10" 2'0"	8'0"	Two	1-3/8" 1-3/4"	14-15/16"	3-17/32" (1'10") 4-17/32" (2'0")	N/A	5-1/4"	3-3/4"	8-1/4"	CB	Smooth
2'2" 2'4"	8'0"	Two	1-3/8" 1-3/4"	18-1/8"	3-15/16" (2'2") 4-15/16" (2'4")	N/A	5-1/4"	3-3/4"	8-1/4"	CB	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	19-11/16"	5-5/32"	N/A	5-1/4"	3-3/4"	8-1/4"	CB	Smooth
2'8"	8'0"	Two	1-3/8" 1-3/4"	22-13/16"	4-1/2"	N/A	5-1/4"	3-3/4"	8-1/4"	CB	Smooth
2'10" 3'0"	8'0"	Two	1-3/8" 1-3/4"	25"	4-1/2" (2'10") 5-1/2" (3'0")	N/A	5-1/4"	3-3/4"	8-1/4"	CB	Smooth

**ROCKPORT™**




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'6" 1'8"	8'0"	Six	1-3/8" 1-3/4"	8-1/2"	4-3/4" (1'6") 5-3/4" (1'8")	N/A	4-5/8"	4-1/4"	10-1/8"	CB	Smooth
2'0" 2'2"	8'0"	Six	1-3/8" 1-3/4"	14-1/2"	4-3/4" (2'0") 5-3/4" (2'2")	N/A	4-5/8"	4-1/4"	10-1/8"	CB	Smooth
2'4"	8'0"	Six	1-3/8" 1-3/4"	18-1/2"	4-3/4"	N/A	4-5/8"	4-1/4"	10-1/8"	CB	Smooth
2'6"	8'0"	Six	1-3/8" 1-3/4"	20-1/2"	4-3/4"	N/A	4-5/8"	4-1/4"	10-1/8"	CB	Smooth
2'8" 2'10"	8'0"	Six	1-3/8" 1-3/4"	22-1/2"	4-3/4" (2'8") 5-3/4" (2'10")	N/A	4-5/8"	4-1/4"	10-1/8"	CB	Smooth
3'0"	8'0"	Six	1-3/8" 1-3/4"	25-3/4"	5-1/8"	N/A	4-5/8"	4-1/4"	10-1/8"	CB	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

SANTA FE™




Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
1'0" 1'2" 1'3" 1'4"	8'0"	Two	1-3/8" 1-3/4"	7"	2-1/2" (1'0") 3-1/2" (1'2") 4" (1'3") 4-1/2" (1'4")	N/A	4-3/8"	7"	9-7/8"	O	Smooth
1'6" 1'8"	8'0"	Two	1-3/8" 1-3/4"	10"	4" (1'6") 5" (1'8")	N/A	4-3/8"	7"	9-7/8"	O	Smooth
1'10" 2'0"	8'0"	Two	1-3/8" 1-3/4"	14"	4" (1'10") 5" (2'0")	N/A	4-3/8"	7"	9-7/8"	O	Smooth
2'2" 2'4"	8'0"	Two	1-3/8" 1-3/4"	18"	4" (2'2") 5" (2'4")	N/A	4-3/8"	7"	9-7/8"	O	Smooth
2'6"	8'0"	Two	1-3/8" 1-3/4"	21"	4-1/2"	N/A	4-3/8"	7"	9-7/8"	O	Smooth
2'8"	8'0"	Two	1-3/8" 1-3/4"	23"	4-1/2"	N/A	4-3/8"	7"	9-7/8"	O	Smooth
2'10" 3'0"	8'0"	Two	1-3/8" 1-3/4"	24"	5" (2'10") 6" (3'0")	N/A	4-3/8"	7"	9-7/8"	O	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 4-1/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

# BIFOLD & COMMERCIAL DOORS

## BIFOLDS




Door Design	Heights*	# of Panels	Thickness	Widths* 2 doors or 1 unit	Widths* 4 doors or 2 units
Avalon°	6'7"; 6'11"	Six	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Caiman°	6'7"; 6'11"	Four	1-3/8"	1'10"; 2'0"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Cambridge™	6'7"; 6'11"; 7'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Camden°	6'7"; 6'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Cararra°	6'7"; 6'11"; 7'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Cashal°	6'7"; 6'11"; 7'11"	Four	1-3/8"	1'10"; 2'0"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Colonial™	6'7"; 6'11"; 7'11"	Six	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Colonist° Smooth	6'7"; 6'11"; 7'11"	Six	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Colonist° Textured	6'7"; 6'11"; 7'11"	Six	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Conmore°	6'7"; 6'11"	Ten	1-3/8"	1'10"; 2'0"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Continental™	6'7"; 6'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Corvado°	6'7"; 6'11"; 7'11"	Four	1-3/8"	1'10"; 2'0"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Coventry°	6'7"; 6'11"; 7'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Craftsman III™	6'7"; 6'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Madison°	6'7"; 6'11"; 7'11"	Two	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Monroe	6'7"; 6'11"; 7'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Princeton™	6'7"; 6'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Provincial°	6'7"; 6'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Rockport™	6'7"; 6'11"	Ten	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"
Santa Fe™	6'7"; 6'11"	Four	1-3/8"	1'10"; 2'0"; 2'2"; 2'4"; 2'6"; 2'8"; 2'10"; 3'0"	3'8"; 4'0"; 4'4"; 4'8"; 5'0"; 5'4"; 5'8"; 6'0"

\* All panel, inner stile, top rail and lock rail measurements will match those listed above. Outer stile measurements may vary 1/4" (depending on pre-fit). All bottom rail measurements will be 1" shorter than the measurements listed above in order to accommodate track and hardware.

Bifolds are available in alternate heights and widths. Please contact JELD-WEN customer service for specifications and availability of alternate sizes. All bifolds are boxed (or end-capped) with track and hardware included.

## COMMERCIAL WIDE STILE



Width	Height	# of Panels	Thickness	Panel Width	Outer Stiles*	Center Mullion	Top Rail	Lock Rail	Bottom Rail	Sticking Profile	Surface
3'0" Cambridge™	6'8" 7'0"	Two	1-3/8" 1-3/4"	23"	6-1/2"	N/A	4-7/16" (6'8") 6"-1/4" (7'0")	6-3/8"	11-11/16" (6'8") 13-7/8" (7'0")	O	Smooth
3'0" Colonial™	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-1/8"	6-7/16"	4-7/8"	4-1/2" (6'8") 6-1/2" (7'0")	6-7/16"	10-9/16" (6'8") 12-9/16" (7'0")	O	Oak Grain
3'0" Colonist°	6'8" 7'0"	Six	1-3/8" 1-3/4"	9-5/8"	6-1/2"	3-3/4"	5-7/8" (6'8") 7-7/8" (7'0")	6-3/4"	10-5/8" (6'8") 12-5/8" (7'0")	CB	Smooth
3'0" Continental™	6'8" 7'0"	Two	1-3/8" 1-3/4"	24"	6"	N/A	5-1/4" (6'8") 7-1/4" (7'0")	4-3/16"	10-13/16" (6'8") 12-13/16" (7'0")	O	Smooth

Sticking Profile: B=Beaded, CB=Cove and Bead, C=Craftsman, S=Stepped, O=Ovolo

\*Assuming standard bore machining (2-1/8" diameter bore), outer stile measurements listed above must be no less than 3-11/16" in order to accommodate a 2-3/8" backset on the lock hole. For 2-3/4" backsets, outer stile measurements must be no less than 3-13/16". If lock bore machining is less than the outer stile measurements listed above, all lock bore drilling must be done within the lock rail for best appearance and performance. Outer stile dimension may vary 1/4" from the measurements listed above.

JWTCDC-90001 03/16