



Premium Aluminum (A-500)

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

Product	AAMA/WDMA/CSA 101 / I.S. 2 / A440 - 05/08/11					
	Configuration	Performance Class and Performance Grade	Max Size Tested	Water Performance (psf)	Air Performance (cfm/ft ²)	Operating Force In Motion (lbf)
Awning	Single Unit	CW - PG30	60x36	4.50	0.3	1
Casement	Single Unit	CW - PG30	36x72	4.50	0.2	5
Fixed	Single Unit	CW - PG50	93x85	6.00	< 0.1	N/A
Horizontal Slider	2 Panel	R - PG20	96x72	3.00	0.2	8
	2 Panel	R - PG30	72x60	4.50	0.2	8
	3 Panel	R - PG20	144x72	3.00	0.2	8
	3 Panel	R - PG30	108x60	4.50	0.2	8
Single Hung	Single Unit	R - PG20	48x96	3.00	0.2	9
Sliding Patio Door	2 Panel	R-PG20	120x120	3.00	0.2	11
	3 Panel	R-PG20	180x120	3.00	0.2	11
	4 Panel	R-PG20	240x120	3.00	0.2	11
Stationary Casement	Single Unit	CW - PG30	60x72	4.50	< 0.1	N/A
590 Sliding Patio Door	NOT RATED					