



PROTECTS AGAINST



DURABLE

100% SURFACE TO CORE PROTECTION

Working with AuraLast Wood is easy. Virtually 100% surface to core protection; nail and screw holes or trimming and sanding will not compromise the shield of AuraLast protection.

TESTED RELIABILITY

AuraLast Wood protects your greatest investment, your home!

PROTECTS AGAINST WOOD ROT. AuraLast Wood achieved highest performance levels to withstand wood rot as measured by the Window and Door Manufacturing Association (WDMA) industry standard.

(WDMA T.M. 1 Soil Block test, AWPA E9-97 and AWPA E10-91)

PROTECTS AGAINST SUBTERRANEAN TERMITES.

Termites cause billions of dollars of damage to homes in the United States every year. And they are aggressive; Formosan Termites can chew through materials such as thin sheets of soft metal, plastics, rubbers, stucco, and styrene to reach their food source.

(Tested to highest levels of performance as measured by AWPA E1-97 standard method for laboratory evaluation to determine resistance to subterranean termites)

PROTECTS AGAINST WATER SATURATION. AuraLast Wood offers superior resistance to water and protects wood against swelling. This helps prevent the door from sticking so it will open and close easily regardless of weather conditions.

(Far exceeds the requirements of WDMA IS-4, T.M. 2 Swellometer Test as measured by anti-swelling efficiency.)

AURALAST® WOOD IS CLEARLY THE SURVIVOR!



AuraLast Wood was put to the test for several years in a very harsh and humid environment. This test hut was built directly on top of a termite colony.



As you can see, after removing the window from its unprotected framework, the AuraLast Wood clearly withstood the harsh elements of wood rot and termite attack.

WE CARE

- » **96% FEWER VOLATILE ORGANIC COMPOUNDS (VOCs)** released during manufacturing process than traditional wood submersion / dip treatment methods
- » **WATER BASED SOLUTION SAFE TO HANDLE** compared to much harsher, solvent based treatments
- » **LONGER LASTING PRODUCTS** mean less waste and more efficient use of our natural resources.

LIFETIME
LIMITED
WARRANTY

For complete warranty information please visit www.jeld-wen.com.



BEAUTIFULLY THE "BEST"

- » AuraLast Wood is **COLORLESS**. *The protective water based solution process does not alter the color of the wood's natural beauty.*
- » AuraLast Wood is **ODORLESS**. *The protective water based solution process does not create offensive odors unlike harsh solvent based treatment methods.*
- » AuraLast Wood door frames; can be **STAINED** to match any wood tone/color application and no pre-sealers are needed.
- » AuraLast Wood door frames; the **COMPLETE FRAME SYSTEM** is protected (top to bottom & surface to the core) from wood rot, termites and water saturation. Unlike other frame systems with a few inches of composite or PVC attached at the bottom leaving over 90% of the frame system unprotected.
- » AuraLast Wood door frames; all **NATURAL WOOD** is much easier to work with compared to other composite or PVC materials.



The JELD-WEN website is your ultimate resource for learning about our reliable windows and doors. It has all the product information and design advice you need. Visit us at jeld-wen.com today.

AuraLast® Wood Exterior Door Frame and Component Specifications



Exterior Door Frame Specifications

- Material:**
- Fingerjoint Primed Paint Grade
 - Natural Wood, Clear Pine, Stain Grade
- Pattern:** Custom
- Thickness & Width:**
- 1-1/4" x 4-9/16"
 - 1-1/4" x 5-1/4"
 - 1-1/4" x 6-9/16"
 - 1-1/4" x 7-1/4"
- Lengths:** 6'8", 7'0" & 8'0" door openings
Lineal
- Options:** Weatherstrip installed
Hinge & Strike Mortise
20-minute fire rating

Exterior Garage Door Frame Specifications

- Material:**
- Fingerjoint Primed Paint Grade
 - Natural Wood, Clear Pine, Stain Grade
- Pattern:** Custom
- Thickness & Width:** 2" x Custom
- Lengths:** Cut to length, Lineal



Exterior Brickmould/Moulding Specifications

- Material:**
- Fingerjoint Primed Paint Grade
 - Natural Wood, Clear Pine, Stain Grade
- Pattern:** Custom
- Thickness & Width:** 1-1/4" x 2"
- Lengths:** 6'8", 7'0" & 8'0" door openings
Lineal



Exterior Center Mull Specifications

- Material:**
- Fingerjoint Primed Paint Grade
 - Natural Wood, Clear Pine, Stain Grade
- Pattern:** Custom
- Thickness & Width:** Custom
- Lengths:** 6'8", 7'0" & 8'0" door openings
Lineal
- Options:** Weatherstrip installed
Hinge & Strike Mortise



Made in the USA



Official window, door and millwork provider of the PGA TOUR and Champions Tour



©2010 JELD-WEN, inc.; Door designs and this publication are owned by JELD-WEN, inc. and are protected under the U.S. Copyright Act and other intellectual property laws. All trademarks, service marks, logos and the like (whether registered or unregistered) are owned or controlled by JELD-WEN, inc. or others. Unauthorized use or duplication of JELD-WEN intellectual property is prohibited.

JELD-WEN reserves the right to change product specifications without notice. Please check our website, jeld-wen.com, for current information.

10-630 12/10 (SB 1M)