

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

Product	AAMA/WDMA/CSA 101/1.S. 2/A440 - 05/08/11 (NAFS 05/08/11)					
	Configuration	Performance Class and Performance Grade	Max Size Tested	Water Performance (psf)	Air Performance (cfm/ft ²)	Operating Force In Motion (lbf)
Awning	Single Unit	LC - PG50	48x36	7.50	0.1	2
	One Wide Two High	LC - PG35	48x96	5.25	0.1	2
Casement	Single Unit	LC - PG50	36x72	7.50	0.1	2
	One Wide Two High	LC - PG35	36x96	5.25	0.1	2
	Two Wide	LC - PG35	72x60	5.25	0.1	2
	Two Wide	R - PG20	72x72	3.00	0.1	2
	Two Wide	LC - PG35	72x60	5.25	0.1	2
	Three Wide	R - PG20	106x72	3.00	0.1	2
	Three Wide	LC - PG35	108x60	5.25	0.1	2
Double Hung	Single Unit	R - PG20	48x77	3.00	0.3	15
	Single Unit	R - PG50	42x57, 38x74	7.50	0.3	15
	Single With Top/Bottom Transom	R - PG20	48x120	3.00	0.3	15
	Single With Top/Bottom Transom	R - PG50	38x108	7.50	0.3	15
	Two Wide	R - PG20	96x77	3.00	0.3	15
	Two Wide	R - PG50	84x57, 76x74	7.50	0.3	15
	Three Wide	R - PG20	120x77	3.00	0.3	15
	Three Wide	R - PG50	114x74	7.50	0.3	15
Double Hung Fixed	Single Unit	R - PG20	72x72	3.00	< 0.1	N/A
	Single Unit	R - PG50	42x74	7.50	< 0.1	N/A
Sliding Patio Door	2 Panel	R - PG20	96x96	3.00	0.1	5
	3 Panel	R - PG20	144x96	3.00	0.1	5
	Single With Top Transom - 2 Panel	R - PG20	96x120	3.00	0.1	5
Stationary Casement	Single Unit	R - PG35	60x72	5.25	< 0.1	N/A
	Single Unit	R - PG50	36x72	7.50	< 0.1	N/A